



HIGHLIGHTS

This all in one point of sale terminal features:

- Intel Celeron processor J1900, elegant, compact, fanless design
- Integrated three track MSR
- Integrated 3" thermal receipt printer
- Integrated customer display 2x20 VFD
- Modular design for easy maintenance
- WLAN, RFID for payment

SPECIFICATIONS



- 15 TFT LCD Touchscreen
- All In One Unit
- Bezel Free

SPECIFICATIONS

CPU:	Intel® Celeron 2.0GHz processor J1900
Chipset:	Intel chipset
LCDK	15" LCD, resolution 1024 x 768 LED backlight LCD
TouchK	Projected Capacitive Touch
Construction:	ABS and metal
Memory:	2G up to 8G (DDR3)
EthernetK	Onboard 10/100/1000 BASE-T Gigabit Ethernet
StorageK	Internal 2.5" type SATA HDD (optional SATA SSD)
External 1/0 InterfaceK	4 • COM ports [COM1-4 on rear 1/0 (COM1-2 powered with DC+0/5/12V, BIOS selection; COM3-4 by Jumper setting) 1 • DB-15 VGA port 1 • DB--25 for LPT port 1 • RJ11 port supports 2 cash drawer(DC+24V) 1 • RJ-45 LAN port with activity and link LEDs 4 • USB 2.0 1 • PS2 Keyboard port 1 • DC +12V input power-jack for adapter
PrinterK	3" Thermal clam shell
MSR:	Three tracks, encryption capable magnetic card reader
Optional:	Customer display module (2 x 20 VFD) or Dual display Pole CD-70 or Pole display RFID WLAN
Operating System:	POS Ready7, Windows 7, Windows 8.1 Industry Pro Retail, Linux (Ubuntu)
Power Supply:	AC100--240V/DC12V, 1 SA, 180W adapter
Operating TempK	0°C~+40°C
CertificationK	CE, FCC, LVD, VCCI, BSMI, 3C