



HIGHLIGHTS

The SP5514 is a cost effective, Windows 10 all in one unit. The terminal is equipped with touchscreen POS functionality, while utilizing a small footprint for counterspace efficiency.

SPECIFICATIONS



- Bezel-free 14" screen with projected capacitive touch (multi-touch)
- Dust & Spray Resistant Front Panel
- Supports (Optional) Customer Facing Display
 - 2x20 Display
 - 11.6" Display
 - 15" Display

SPECIFICATIONS

CPU:	Intel®Celeron™ J1900 (2.00GHz). quad core, 2MB L2 cache. fanless
LCDK	Bezel-free 14" TFT-LCD. Resolution 1366 x 768. LED backlight
TouchK	Projected Capacitive Touch (multi -touch)
RAM:	4GB DDR3L SO-DIMM
Storage:	64G SSD or 2.5" SATA Hard Drive
LANK	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet
SpeakerK	1 x 3W speaker (internal)
I/O InterfaceK	2 x COM (DC+0/5/12V: COM 1-2 BIOS selection) 3 X USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 xVGA 1 x DC+ 12V Out 1 :x Mini PCI-e (internal) 1 x Audio connector
Optional:	1. RS-232 COM 089 x 2 (OV/5V/12V selection by jumper). 2.Or RS232 COM x 1 (0B9. OV/5V/12V selection by JP) 3.Or Powered USB 12V x 3 & 24V x 1 PCBA (max 72W) 4.Or 1 x COM (OV/5V/12V selection by jumper)+ USB 2.0 x 2
Operating System:	Windows 10
Power Supply:	AC100-240V/DC+ 12V. 65W / 90W / 180W power adapter
Operating TempK	32°F -104°F
Optional PeripheralsK	3-track MSR 2x20 line display Customer facing displays: 11.6" or 15"
ColorK	Black