

# SP-5514 TOUCH POS SYSTEM

ADVANCED POS FUNCTIONALITY WITH STYLE



The Partner Tech SP-5514 touch screen terminal packs POS functionality into a modern, sleek design that compliments the décor of even the most stylish restaurants and retail settings. With five color options to choose from the SP-5514 compliments any store style and design.

## POS that Works Almost Anywhere

The SP-5514 features a small footprint that can be used even where space is limited.

## Not Just a Pretty Face

The SP-5514 has been designed to optimize workflows at the checkout. The 14-inch-wide, 16:9, PCT touchscreen makes it easy for your staff to use – even new employees can use intuitive touchscreen interfaces efficiently almost from day one.

### SPECIAL FEATURES

Bezel-free 14" screen with projected capacitive touch (multi-touch)

Dust-and spray-resistant front panel (IP65)

### OPTIONAL

Available in Classic Black.

Supports optional customer-facing display (2x 20 VFD, 7", 11.6" or 15")

SP-5514



Ready Theatre Systems  
(865) 212-9703 Ext. 140  
sales@rts-solutions.com

**SP-5514**

Item	SP-5514						
CPU	Intel® Celeron™ J1900 (2.00GHz), quad core, 2MB L2 cache, fanless						
LCD	Bezel-free 14" TFT-LCD, resolution 1366 x 768, brightness 220cd/m², LED back-light						
Touch	Projected Capacitive Touch (multi-touch)						
RAM	4GB DDR3L SO-DIMM						
Storage	64G SSD or 2.5" SATA Hard Drive						
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet						
I/O Interface	2 x COM (DC+0/5/12V: COM 1-2 BIOS selection) 3 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x Audio connector						
Optional Interface Expansion	1. RS-232 COM DB9 x 2 (0V/5V/12V selection by jumper) , 2. Or RS232 COM x 1 (DB9, 0V/5V/12V selection by JP) 3. Or Powered USB 12V x 3 & 24V x 1 PCBA (max 72W) 4. Or 1 x COM (0V/5V/12V selection by jumper) + USB 2.0 x 2						
Speaker	1 x 3W speaker (internal)						
Operating Systems	Windows 10						
Power Supply	AC100~240V/DC+12V, 65W / 90W / 180W power adaptor						
Dimensions	14.45in (W) x 9.92in (D) x 11.69in (H)						
Environment	<table border="0"> <tr> <td>Temperature:</td> <td>Operating: 32°F - 104°F</td> <td>Storage: -4°F - 140°F</td> </tr> <tr> <td>Humidity:</td> <td>15% - 80%</td> <td>15% - 80%</td> </tr> </table>	Temperature:	Operating: 32°F - 104°F	Storage: -4°F - 140°F	Humidity:	15% - 80%	15% - 80%
Temperature:	Operating: 32°F - 104°F	Storage: -4°F - 140°F					
Humidity:	15% - 80%	15% - 80%					
Optional Peripherals	3-track MSR 2x20 line VF display Customer facing displays: 7", 11.6" or 15"						
Color	Black						

\*Specification is subject to change without prior notice

